









Neon Flex Compatibility List							
1st August 2017							
Part number							
24VDC PSU							
Outdoor							
24VDC RGB							
LED-RGB-NF-PC-4FT	mains leads 4 foot						Use only for RGB
LED-RGB-NF-EXT-2FT	Extension cable 2 foot						Use only for RGB
LED-RGB-EC	RGB End Cap						Can also be used with Standard, Mini, Super and 360. *
RGB-CH-AL	RGB Aluminium Chanel (per metre)						Use only for RGB
RGB-PVCTUBE-5	Extra RGB Heat Shrink bag of 10 (supplied one per join FOC)						Can be used for all Types
LED-RGB-NF-FC	Extra RGB Pins (supplied one per join FOC)						Use only for RGB
LED-RGB-NF-CL	Mounting Clips (bag of 10)						Use only for RGB
Standard , Mini and 360 Shape							
PC-24V-2FT-S	24VDC 600mm DC front connector						Standard can be used also with Mini and 360 degree* Mini and 360 can only be used with their own Neon Flex
LED-NF-PC-240V-4FT-S	AC Power Connection with 4FT PVC Cable, (to connect to 240VAC Neon)						Standard can be used also with Mini and 360 degree* Mini and 360 can only be used with their own Neon Flex
LED-NF-FC	Extra Pins (supplied one per join FOC)						Can be used with all but RGB
LED-NF-EXT-C-2FT-S	Extension cable 2 foot						Standard can be used also with Mini and 360 degree* Mini and 360 can only be used with their own Neon Flex
LED-NF-EC-S	End Cap						Standard can be used also with Mini and 360 degree* Mini and 360 can only be used with their own Neon Flex

PVCTUBE	Extra Heat shrink bag of 10 (supplied one per join FOC)		Can be used with all
LED-NF-CH-P-S	Plastic Channel (per metre) for Standard or mini		use only the channel for each shape
LED-NF-CH-AL-S	Aluminium channel (per metre) standard only		use only the channel for each shape
LED-NF-CH-AL-BK-S	Black Aluminium channel (per metre) standard only		use only the channel for each shape
KNL-NF-CL-S	Mounting Clip (Bag of 10 pieces)		use only the Mounting Clips for each shape
KNL-NF-PIN-PC	right angle pin connector (600mm of cable)		For 24VDC only Can be used with all 24VDC products RGB requires 2
KNL-NF-PIN-EXT	extension Pin connector (600mm of cable)		For 24VDC only Can be used with all 24VDC products RGB requires 2
Water Proof Items			
Loctite 595	Silicon Adhesive 100ml (should do 6-10 joins)		Can be used for all Types
WP-CAB	Water-proof Cable connector (to connect a 24VDC PSU to a DC front connector (KNL-NF-PC-24V).		Use to connect to a IP67 power supply and all DC front connectors
WP-HS	Water Resistant Heat shrink 60mm (1 required for every join)		Use on all joins end cap and front connectors in conjunction with the silicone to water proof the neon flex.
* Note. If used with the other types you will require more Silicone to make water proof Joins as the gap will be larger between the neon and the connector.			